



MAREN
Balers & Shredders
Building customer loyalty since 1962.

 **KERNIC**
S Y S T E M S

ProPAK 2R425

two ram baler



SMART Bale
intelligent baler control

When there's TONS of work to be done, work smarter with our app! With Maren's Optional Smartbale Mobile Remote interface you can monitor and control the operation of your ProPak two ram baler with a portable full color touch screen. Easily monitor bale size and statistics, read messages, clear jams and change materials safely from the seat of your loader. *That means your loader operator is now your baler operator too!*

FEATURES:

- : Large "Wide Box" (57" W x 100" L), clear opening with standard tongue and groove floor, ideal for both post-Industrial cardboard and scrap metals, while easily processing paper, fiber, plastic and other recyclables.
- : Interlocking plate steel construction distributes stresses away from welds to tabbed locking joints.
- : Chassis floor and sides constructed of seamless single sheet plate steel.
- : Replaceable "AR" hardened wear liners allow for limitless replacement of all chassis wear surfaces for years of reliable service.
- : Multi edge replaceable shear blades reduce cost by allowing blade rotation to gain additional new cutting edges before blade replacement. Extended progressive cutting profile shears material over a long distance effectively reducing shear jams.
- : 600-900 gallon floor mounted hydraulic oil reservoir. Hydraulic oil is an available option.
- : Clogged oil filter sensor, high oil temp sensor and low oil level sensors automatically protect your investment while notifying the operator attention is needed.
- : Robust ram and door position transducers allow automatic control of bale size, final bale finishing, shear jam prevention, wire placement and bale ejection.
- : Bale separation door facilitates instant material changes and virtually eliminates cross contamination between bales. The door's transducer positioning allows up to 13" oversized bales to eject without jam, yet closely guides the bale to the tier for tight bales and reduced falloff.
- : All safety E-Stops and contactor resets monitored by a dual redundant safety relay system.

CHASSIS

Height
w/ conveyor – 165"
w/o conveyor – 85.5"

Width
w/o bale table – 197"

Length –
w/o conveyor – 33'

Baler shipping
weight – approx. 95,000 lbs.



Never get caught empty handed with a blown fuse! Electrical panel employs service friendly molded case and mini circuit breakers for all circuits both main and branch.*

* (Except where unavailable for 600 volt systems)



11" main-ram cylinder with 427,649 lbs. of platen force delivers up to 30% more force than competitive balers using 11" cylinders.



PERFORMANCE DATA:

Motor : Dual 50hp, Triple 50hp, or Triple 75hp TEFC 3 Phase motors generate 100, 150 or 225hp. Motors automatically stage start to reduce surge on electric service. During low production demand motors can be de-selected to reduce overall electrical consumption and throughput while maintaining 100% bale weights and shearing performance.

Hydraulic : A simple but innovative hydraulic system allows the 2R425 to run faster and more efficiently while being more serviceable. highly efficient piston pumps rated for 6,100 psi run at only 4,500 psi ensuring less stress and long life. All pumps are mounted below tank level to eliminate start up cavitation and extend pump life.

Hydraulic System : High Efficiency Regenerative.

Platen Force : 427,649 lbs.

Platen Pressure : 250 psi.

Dry Cycle Time at full penetration :

21 seconds (100hp) – 14.5 seconds (150hp) and – 14.5 seconds (225hp)

TOUCH SCREEN OPERATOR INTERFACE:

: Maren's SmartBale Intelligent baler control allows password protected saving of a complete set of parameters for each commodity to be baled. At run time the operator simply selects the proper material from a drop down list and the ProPak 2R425 automatically configures for the commodity to be baled. Settings automatically adjusted include wire count, wire placement, baling pressure, bale size, photo eye selection, conveyor speed, multi motor settings and many more.

: Displays statistics such as current bale size, remaining for full bale, average charge and largest charge, all helping the baler operator make easy cleanup free material changes.

: Password protected maintenance screens accessible to onsite maintenance staff allow further customization and simplify trouble shooting with trouble shooting screens for inputs, outputs and other statistics.

BALE WEIGHTS *

OCC	1,700 lbs.
MIXED PAPER	1,700 lbs
MAGAZINES	2,000 lbs.
ALUMINUM CANS	1,100 lbs.
ALUMINUM EXTRUSIONS	1,400 lbs.
ALUMINUM SIDING/SHEET	2,000 lbs.
TIN CANS	2,200 lbs.
NON INSULATED COPPER WIRE	6,000 lbs.
#1 COPPER	4,000 lbs.
MSW	2,400 lbs.
HDPE	1,500 lbs.
PET	1,300 lbs.

(percentage of caps on bottles will vary bale weights)

BALE SIZE :

Length	60"
Width	38" - 51" (*OS)
Height	30"

* Bale Weights are approximate, and may differ with moisture content, material density, etc.

* Due to Maren's commitment to product quality and refinement, these specifications are subject to change without notice, and without incurring responsibility to units previously sold.

IF YOU THOUGHT YOU KNEW MAREN—LOOK AGAIN



MAREN
Balers & Shredders
Building customer loyalty since 1962.

**The ONE SOURCE for innovation
for your Waste Management System.**

Your authorized dealer



+1(800) 678-9516
+1(905) 632-0562

www.kernicsystems.com
sales@kernicsystems.com

5230 South Service Road,
Burlington, ON, L7L 5K2, Canada