A265)	DESCRIPTIONS	A285)
39.5" or 42.5"	Feed Opening – Width	39.5" or 42.5"
48", 64", 80"	Feed Opening – Length	64" or 80"
42"	Feed Opening – Depth	42"
9"	Main Cylinder	9"
4200 PSI	Operating Pressure	4500 PSI
267,192 lbs	Ram Force	286,315 Lbs
141 PSI - 45 Wide 151 PSI - 42 Wide	Baling Force	151 PSI - 45 Wide 164 PSI - 42 Wide
Twin 30's	Horsepower Options	Twin 40's, Twin 50's, Twin 60's, Triple 50's
15 secs to 20.4 secs	No Load Cycle Time	7.5 secs. to 10.6 secs.
Up to 14,400 cf/hr	No Load Displacement	Up to 42,000 cf/hr
42 x 42 x Variable or 45 x 42 x Variable	Bale Size	42 x 42 x Variable or 45 x 42 x Variable
OCC – 33#/cf	Typical Bale Density	OCC – 34#/cf





BOTH MODELS **INCLUDE:**

PLC :

Closed loop air oil cooler w/ independent circulation pump **Oil Cooling** Allen-Bradley Micrologix 10.4" Allen-Bradley Panelview Plus 7 color touch screen AR400 replaceable floor liners Full tank of oil shipped with baler Bale wire run out sensor 10' heavy duty bale run out slide



vements and changes, the features and specifications in this brochure are subject to change without notice. Because of Ma ous product impro



www.kernicsystems.com sales@kernicsystems.com Authorized Distributor **KERNIC**

+1(905) 632-0562 5230 South Service Road, Burlington, ON, L7L 5K2, Canada

Corrugated Box Folding Carton Printing Converting Tissue Envelope Materials Recycling Facility (MRF)

2. 10-1-18



Advanced Auto-tie SHEAR Balers



Fewer Jams Less Cleanup Longer Lasting Easier Servicing Heavier Bales



Maren Balers have long been regarded the standard of the box, printing, and process industries.

The Maren ProPAK-A SERIES takes that standard to an even higher level. These balers are built specifically for the difficult duty cycle required in corrugated box, folding carton, printing, converting, envelope and tissue industries. If you run a high volume operation and things like bale weight, up time, durability, safety, serviceability and cleanliness keep you up at night take a good look at the Maren ProPAK-A SERIES.

With multiple horsepower options and several hopper sizes to choose from these workhorse's fulfill virtually any production requirements.

FEATURES:

- : "A" Frame single cylinder tension chamber takes advantage of maximum ram force during full pressure baling.
- Bale sizes up to 45"w x 42"h x variable length producing bales over 3000 lbs.
- : Hopper sizes to adapt with any air conveying system
- : Advanced automatic 6-wire bale tier with electrically driven inserter and twister.
- : Optional 1000# bulk wire feed system.
- : Optional easy lifting electric hoist wire loading boom.
- : Advanced progressive shear blade design with 30" penetration reduces shear jams and utilizes maximum ram pressure for compaction. Maren shear blade is a replaceable double edge design made of hardened and ground tool steel.

- Interlocking baler chassis and ram is constructed of high strength plate steel, significantly increasing the strength of welded joints.
- : High strength steel plate floor is further reinforced with a replaceable AR400 abrasion resistant wear plate for ultimate durability, and virtually limitless service life.
- : Sealed tight and serviceable, the main ram is guided and sealed on bottom and sides by long wearing NylOil wear plates. The top of the ram is sealed tight with a spring loaded AR400 scraper. This provides unparalleled sealing and prevention of material migration behind the ram.
- : Chassis service door for easy access ahead and behind main ram. Door is electronically interlocked and can be padlocked to provide secure access only by maintenance personnel.
- : Maren's exclusive key lock main cylinder mount removes main cylinder tension from bolts while allowing easy services and maximum cylinder mount durability.





TOUCH SCREEN OPERATOR INTERFACE:

: 10.4" Allen-Bradley Panelview Plus 7 color touch screen.

- Displays the baler's current status and indicates bale percentage complete with graphic progress bar.
- : Allows selection of saved material settings controlling bale length, photo eye options, etc.
- Dual motor models when equipped, allow the operator to select either motor/pump A or B to operate, or allow automatic on demand activation of second motor.

- : Displays and stores machine faults, E-stop status and allows service personnel to display a fault message history log.
- : Optional conveyor controls allow operator to select upper or lower photo eye activation, run, jog, stop, conveyor auto stop delay and more.
- : Password protection allows operators to access run time features while blocking service only adjustments for authorized maintenance.

Hardened tool steel progressive shear blade and 30" penetration all but eliminates shear jams.





Lower ram chassis inspection door for easy maintenance access.

PROPAK SHEAR BALERS - LEADING THE WAY IN PAPER CONVERTING BALING

www.kernicsystems.com

sales@kernicsystems.com

Maren's unique 100% gear driven twister maintains timing and avoids problems common with chain driven systems.

Key lock cylinder design provides maximum cylinder mount durability and allows easy maintenance access.

Raiser kit allows for easy cleaning and clearing around baler.

+1(905) 632-0562